



1. HIGH TENSION CABLE BARRIERS (HTCB) ARE PROPRIETARY PRODUCTS AND THEREFORE MUST BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURER'S AND/OR VENDOR'S SPECIFICATIONS. CABLE BARRIER PRODUCTS VARY SUBSTANTIALLY IN DETAILS, SPECIFICATION AND METHOD OF INSTALLATION, ETC. DESIGNERS SHALL REVIEW THE FHWA (UNITED STATES FEDERAL HIGHWAY ADMINISTRATION) ACCEPTANCE LETTERS IN CONJUNCTION WITH THE MANUFACTURER /VENDOR'S PRODUCT DETAILS AND SPECIFICATIONS.
2. DESIGNERS SHALL REVIEW THE FHWA ACCEPTANCE LETTERS, AND THE TEST DOCUMENTATION UPON WHICH THE LETTER IS BASED IN DETAIL. THIS INCLUDES THE SUMMARY RESULTS (E.G. TEST DEFLECTION), TEST SITE CONDITIONS (E.G. POST SPACING, SOIL DATA, ETC.), PRODUCT DETAILS, PROVISIONS, ETC. IN WHICH THE PRODUCT WAS TESTED AND ACCEPTED UNDER.
3. FHWA ACCEPTANCE LETTERS ARE NORMALLY BASED ON THE HTCB SYSTEM BEING TESTED ON TANGENT IN A CONTROLLED ENVIRONMENT. THE SLOPE PLACEMENT, POST SPACING AND MAXIMUM SPECIFIED, DEFLECTION ETC. MAY NEED TO BE ADJUSTED DUE TO SITE SPECIFIC CONDITIONS.
4. HTCB TYPICALLY SHOULD BE PLACED UNDER THE FOLLOWING CONDITIONS:
  - AT THE EDGE OF THE SHOULDER BREAKPOINT (0 m LATERAL OFFSET).
  - THE OPTION OF TWO SEPARATE LONGITUDINAL RUNS OF HTCB SHOULD ALSO BE CONSIDERED WHERE THE MEDIAN WIDTH IS NARROW, DESIRABLE DEFLECTION SPACE IS GREATER THAN THE SHOULDER WIDTH, AND/OR GENERAL RE-GRADING IS NOT AN OPTION, ETC.
5. NO ZONE. AREA IN THE MEDIAN WHERE HTCB TYPICALLY SHOULD NOT BE INSTALLED.
6. POSTS CAN BE PLACED IN SOCKETS IN CONCRETE FOUNDATIONS OR SOCKETS DRIVEN INTO THE GROUND DEPENDING ON THE SOIL CONDITION, MANUFACTURER'S SPECIFICATION AND FHWA APPROVALS. POSTS DRIVEN DIRECTLY INTO THE GROUND ARE NOT PERMITTED.
7. THE DITCH MAY BE SUBJECT TO WEAK SOILS (OFTEN UNCOMPACTED), PERIODIC FLOODING AND/OR WET SOIL CONDITIONS. THE SOIL STRENGTH MUST BE TAKEN INTO ACCOUNT WHEN DESIGNING THE POST FOUNDATIONS AND END ANCHOR FOUNDATIONS.
8. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE NOTED.

4			
3			
2			
1			HC
No.	REVISIONS	BY	DATE

Steve Otto For Executive Director, Technical Standards Branch	<b>Government of Alberta</b> Transportation
Date: 17 February, 2012	
<b>TYPICAL HIGH TENSION CABLE BARRIER MEDIAN INSTALLATION</b> <b>SLOPES STEEPER THAN 4(H):1(V)</b>	

Prepared By: GEC.	Checked By: PM	Scale: N.T.S.	Dwg No.: RDG-B2.3
-------------------	----------------	---------------	-------------------